

IN THE CLAIMS

1-5 (Canceled).

6. (Currently Amended) The terminal equipment for cable television according to claim 15, wherein said controller switches ~~[[a]]~~ the selector subsection of said second tuner section in response to a manipulation signal input thereto, to supply the image signal from said second tuner section to said radio-transmitter section or ~~[[a]]~~ the terminal connected to ~~[[a]]~~ the picture-recording device.

7-13 (Canceled).

14. (Previously Presented) The terminal equipment for cable television according to claim 15, wherein said slave terminal further includes a remote controller receiving section for receiving a remote control signal supplied from a wireless remote controller.

15. (Currently Amended) Terminal equipment connected to a cable television station of cable television to receive a cablecast signal for television programming delivered from the cable television station, comprising:

a master terminal including a first tuner section for receiving a cablecast signal for television programming delivered from the cable television station and applying an image signal produced from the cablecast signal to a first television receiver, at least one second tuner section for receiving a cablecast signal for television programming

delivered from the cable television station and outputting an image signal produced from the cablecast signal, and a radio-transmitter section connected to said second tuner section to radio-transmit the image signal output from the second tuner section, wherein said second tuner section has a selector subsection for switching between a terminal connected to a picture-recording device and said radio-transmitter section to apply the image signal to the terminal or said radio-transmitter section;

at least one slave terminal including a radio-receiving section for receiving the image signal transmitted from said radio-transmitter section of said master terminal, and applying the image signal received by said radio-receiving section to a second television receiver; and

a message signal outputting section for outputting a message signal for displaying a selecting state of said selector subsection on the second television receiver, to transmit the message signal through said radio-transmitter section to said slave terminal, the message signal indicating that the image signal is prevented from being transmitted when the selector subsection is switched to send the image signal from said second tuner section to the picture-recording device.